



NOTE: THE OVERLOAD CAPACITIES FOR BENDING MOMENT, AXIAL AND RADIAL FORCE EXCEED 150% OF THOSE USED FOR CROSSTALK MEASUREMENT

FOR HD CSG-17-XXX-2A-GR-BB-LW

DRAWING IN THIRD ANGLE PROJECTION

ATTENTION: RED WIRE MUST BE CONNECTED TO POSITIVE SUPPLY VOLTAGE AND BLACK TO GROUND. OTHERWISE CIRCUIT MAY GET DAMAGED!

* WHEN PWR SUPPLY IS 4.5V, OUTPUT WILL BE 2.25±1.75V

WIRING CODE

COLOR	FUNCTION
RED	+EX
GREEN	+SIG
BLACK	GND
BROWN	-SIG

SPECIFICATIONS

CAPACITY (Nm)	80
OVERLOAD CAPACITY (%F.S.)	250
DIFFERENTIAL OUTPUT @ F.S. NOMINAL V	2.5±2 *
POWER SUPPLY (V)	4.5 TO 5V
BRIDGE RESISTANCE (Ω) NOMINAL	350
NON-LINEARITY (%F.S.)	0.5
HYSTERESIS (%F.S.)	1.0
OPERATING TEMP. RANGE (°C)	-20 TO +100
CROSSTALK (%F.S.)	1.0
AXIAL FORCE FOR CROSSTALK (N)	400
RADIAL FORCE FOR CROSSTALK (N)	400
BENDING MOMENT FOR CROSSTALK (Nm)	16
TORSION ANGLE (CALCULATED)	0.06°
TORSIONAL STIFFNESS (KNm/RAD)	76
BENDING STIFFNESS (KNm/RAD)	12
MASS (KG)	0.075

SUNRISE INSTRUMENTS

www.srisensor.com

ROBOT JOINT TORQUE LOADCELL
D55MM, 80 Nm, FOR HD CSG-17

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN MM

M2212P3

REV.
A